

AMENDMENTS TO THE CLAIMS

1. (Original) A device for optical coupling comprising
first and second optical waveguides (13, 23) extending longitudinally with cores (14, 24) adapted to guide optical radiation (15),
first resonator means, laterally surrounding the first waveguide, comprising first and second resonator members (18, 19), and second resonator means, laterally surrounding the second waveguide, comprising third and fourth resonator members (28, 29),
characterised in that
first and second deflector means (16, 26), adapted to couple radiation propagating in the respective first and second waveguides with common radiation modes (30), which modes are defined by adjustable geometrical and material properties of the device, so as to obtain wavelength selective coupling of radiation guided by the first and second waveguides, provided the resonator means are tuned to the same resonance wavelength.
2. (Original) A device for optical coupling according to claim 1, **characterised in that**
at least one of the waveguides comprise optical fibers or planar optical waveguides.
3. (Original) A device for optical coupling according to claim 1, **characterised in that**
at least one of the deflector means includes a periodic refractive index modulation grating, preferably inscribed in the light-guiding regions of said optical waveguide.
4. (Original) A device for optical coupling according to claim 3, **characterised in that**
the deflector means includes optical Bragg grating, preferably tilted.
5. (Original) A device for optical coupling according to claim 1, **characterised in that**
comprised optical elements, such as the resonator means, the optical waveguides and the deflector means are arranged to have mirror symmetry with respect to a plane defined by the longitudinal and transverse optical axes (1, 2).

6. (Currently amended) A device for optical coupling according to ~~any of preceding claims~~
claim 1, characterised in that
at least one of the resonator members is a mirror chosen from a group consisting of:
dielectric multilayer mirror, metal mirror and metal mirror with dielectric coating.
7. (Original) A device for optical coupling according to claim 1, **characterised in that**
a separation between the first second resonator means provides an internal resonator
means, and
the separation is selected to locate the internal resonator resonance at wavelengths outside
the range in which the resonator means are made resonant.
8. (Original) A device for optical coupling according to claim 1, **characterised in that**
the resonance wavelength of each of the resonator means is controllable by adjusting the
optical distance, i.e. the product of the geometrical distance and refractive index, between the
first and second resonator members and the third and fourth resonator members, respectively.
9. (Original) A device for optical coupling according to claim 1, **characterised in that**
the resonator means are made resonant to radiation having a wavelength within the range
of 1,260 to 1,675 μm .
10. (Original) A device for optical coupling according to claim 1, **characterised in that**
the resonator means are made resonant to radiation having a wavelength within anyone of
the ranges of: 1,260 to 1,360 μm (O-band), 1,360 to 1,460 μm (E-band), 1,460 to 1,530 μm
(S-band), 1,530 to 1,565 μm (C-band), 1,565 to 1,625 μm (L-band) or 1,625 to 1,675 μm (U-
band).
11. (Currently amended) A device for optical coupling according to claim 3 ~~or~~ 4, **characterised
in that**
the respective deflector means include two superposed Bragg gratings, having essentially

orthogonal grating vectors.

12. (Original) A device for optical coupling according to claim 11, **characterised in that** the superposed gratings are adapted to deflect light in the same longitudinal direction but in opposite transverse directions and simultaneously collect light arriving from the same longitudinal direction but from opposite transverse directions.
13. (Original) A device for optical coupling according to claim 3, **characterised in that** the deflector means includes transversally asymmetric optical Bragg grating.
14. (Original) A device for optical coupling according to claim 1, **characterised in that** at least one of the deflector means includes a grating comprising blazed corrugations having alternating projections and spaces along a wall parallel to the longitudinal axis of the respective waveguides.
15. (Original) A device for optical coupling according claim 11, **characterised in that** interference between waves coupled out from each of the gratings is controllable by adjusting the geometrical position or refractive index of any of the waveguides the resonator means.
16. (Currently amended) A device for optical coupling according to ~~any one of claims 8 or 15~~ **claim 8**, **characterised in that** the refractive index is controllable by adjusting at least one parameter chosen from a group consisting of : temperature, injection of charge carriers, application of an electric voltage and application of mechanical stress.
17. (Currently amended) A device for optical coupling according to ~~any one of preceding claims~~ **claim 1**, **characterised in that** the spectral selectivity is controllable by changing mirror separation along the

longitudinal optical axis for the first and second resonator means, or by having a chirped grating period in the first and second deflector means.

18. (Original) A device for optical coupling according to claim 1, **characterised in that** beam transformation means is arranged between the resonator means to reduce transverse beam divergence, whereby the means is chosen from a group comprising: a conventional, preferably cylindrical, lens, a Fresnel lens, a refractive or diffractive optical element.
19. (Original) A device for optical coupling according to claim 1, **characterised in that** each of the first and said second resonator means has different optical thickness, while being resonant for the same wavelength.
20. (Original) A device for optical coupling according to claim 1, **characterised in that** the orders of resonance of at least one of the resonator means is adjustable so as to tune the coupling wavelength.
21. (Currently amended) An array of devices for optical coupling according to ~~anyone of preceding claims~~ claim 1, **characterised in that** each device for optical coupling is adapted to couple any wavelength within a predetermined wavelength range.
22. (Currently amended) A method of fabricating a device for optical coupling according to ~~anyone of preceding claims~~ claim 1, **characterised by** sandwiching two essentially identical structures, each including an external resonator and an optical waveguide with a deflector.

23. (Currently amended) Use of a device for optical coupling according to ~~anyone of claims 1-20~~
claim 1 as a two-port spectrally tunable transmission filter.

24. (Currently amended) Use of a device for optical coupling ~~according to anyone~~
~~of claims 1-20~~ claim 1 as a two-port spectrally selective attenuator.